

[Bill's Saw Shop](#) <-(click to return to main page)

Husqvarna chain saw specifications by model

Rev. 7/2008 - LCS - Bill's Saw Shop

This is an unofficial list! Use it at your own risk.

Model	C.I.	C.C.	H.P.	LBS.	Initial H	Initial L	Idle Speed	Max RPM
23	-	38	-	-	1	1	2,500	11,000
36 (pre-97)	-	36	-	-	1	1	3,000	13,000
36 (97 & up)	-	36	-	-	2	1.5	3,000	13,000
40	-	40	-	-	1	1	2,500	12,500
41 (pre-97)	-	40	-	-	1	1	3,000	13,000
41 (97 & up)	-	40	-	-	2	1.5	3,000	13,000
42	-	42	-	10	1	1	2,700	13,500
45 (pre-97)	-	44	-	-	1	1	2,500	12,500
45 (97 & up)	-	44	-	-	1.25	1.5	2,500	12,500
49	-	49	-	-	1.25	1.5	2,500	12,500
51	3.1	51	3.1	11.4	1.25	1.25	2,500	12,500
55	3.2	53	3.4	11.4	1.25	1.25	2,700	12,500
55R	3.2	53	3.4	11.4	1.25	1.25	2,700	12,500
61	3.75	61.5	4.1	12.8	1	1	2,500	12,500
136	2.2	36	2.2	10.1	2	1 1/2	3,000	13,000
137	2.2	36	2.2	10.1	2	1 1/2	3,000	13,000
141	2.4	40	2.6	10.1	2	1 1/2	3,000	13,000
142	2.4	40	2.6	10.1	2	1 1/2	3,000	13,000
242XP	2.5	42	3.1	10.3	1	1	2,700	15,500
257	3.5	57	3.8	12.0	1	1	2,700	13,000
261	3.8	62	-	13.0	3/4	1 1/4	2,700	13,000
262XP	3.8	62	4.8	12.0	1	1	2,700	13,500
268	4.1	67	4.7	13.7	1	1	2,500	12,500
268K	-	67	-	-	1	1	2,500	10,000
272XP	4.4	72	5.2	13.7	1	1	2,500	13,500
281XP	4.9	81	5.7	15.0	1	1	2,500	12,500
288XP/Lite	5.4	88	6.1	15.9	3/4	1 1/2	2,500	12,500

Model	C.I.	C.C.	H.P.	LBS.	Initial H	Initial L	Idle	Max
-------	------	------	------	------	-----------	-----------	------	-----

							Speed	RPM
334T	2.2	35	2.0	7.7	1 1/2	1 1/2	2,800	13,800
335XPT	2.2	35	2.1	7.5	3 1/2	1 3/4	2,800	13,800
336	2.2	35	2.0	8.4	1 1/2	1 1/2	2,800	13,800
338XPT	2.4	39	2.3	7.7	1 1/2	1 1/2	2,800	13,800
340	2.5	41	2.7	10.4	1	1	2,700	12,500
345	2.7	45	3.0	10.4	1	1	2,700	12,500
346XP	2.7	45	3.4	10.6	1	1	2,700	14,700
350	3.0	50	3.1	10.6	1	1	2,700	13,000
351	3.0	50	3.1	10.6	1	1	2,700	13,000
353	3.2	52	3.3	11.0	1	1	2,700	13,000
357XP	3.5	57	4.4	12.1	1	1	2,700	14,000
359	3.6	59	3.9	12.1	1	1	2,700	13,500
362XP	4.0	65	4.6	13.2	3/4	1	2,700	13,500
365	4.0	65	4.6	13.2	3/4	1 1/2	2,700	12,500
371XP	4.3	71	5.4	13.4	3/4	1	2,700	13,500
371K	4.3	71	5.4	20.7	5/8	1 1/8	2,500	10,000
372XP	4.3	71	5.4	13.4	3/4	1	2,700	13,500
385XP	5.2	85	6.3	15.4	1 1/4	1 1/4	2,700	13,000
390XP	5.4	88	6.5	15.6			2,700	13,000
394XP	5.7	94	7.1	17.4	3/4	1 1/2	2,500	12,500
395XP	5.7	93.6	7.1	17.4	-	-	2,500	12,500
455	3.4	55.5	3.4	13.0	2 1/2	1 1/2	2,700	13,500
570	4.1	68	4.9	14.9	2	1 1/2	-	13,500
575XP	4.48	73.5	5.4	14.9	3	1 1/2	-	13,500
3120XP	-	119	-	-	FIXED	1	2,500	11,000